

M/T *Thalassa Desgagnés*



Desgagnés Tanker Inc.

21 Marché-Champlain Street, Suite 100
 Québec (Québec) Canada G1K 8Z8
 Tel: (418) 692-1000 • Fax: (418) 692-6044
 Telex: 051-2212 • E-mail: info@desgagnes.com

Commercial Operator : Petro-Nav Inc., Montréal
 Tel: (514) 843-8800
 Fax: (514) 843-9195
 Built: Ankerløkken, Norway, 1976
 Rebuilt: MIL Davie, Canada, 1993
 Official No.: 399944
 IMO No.: 7382988
 Call Sign: VORX
 Port of Registry: Québec
 Flag: Canadian
 Type: Tanker for HFO and asphalt
 Class: Lloyd's 100A1, ESP, Ice 1A, LMC, UMS

MAIN PARTICULARS

GRT: 5,746
 NRT: 3,048
 Deadweight: 9,748
 LOA: 134.54 m 441.40 feet
 LBP: 127.20 m 417.32 feet
 Breadth: 17.20 m 56.43 feet
 Moulded Depth: 10.00 m 32.81 feet
 Summer Draught SW: 7.92 m 25.98 feet

COMPLIANCE WITH REGULATIONS

World-wide trading: Solas, Marpol, ISM, USCG
 for foreign flag, Suez, Panama;
 St. Lawrence Seaway

TANK CAPACITY	1		2		3		4		5		6		7		8		TOTAL	
	Port	Starboard	Port	Starboard	Port	Starboard	Port	Starboard	Port	Starboard	Port	Starboard	Port	Starboard	Port	Starboard	M ³	US BBLs
100% (in m ³)	244	244	506	506	636	636	804	804	805	805	675	675	621	621	1,084	1,029	10,695	67,269
98% (in m ³)	239	239	496	496	623	623	788	788	789	789	661	661	609	609	1,062	1,008	10,480	65,917

- ◆ Double hull, SBT
- ◆ Three cargo segregations
- ◆ Thermal oil heating coils for cargo and ballast tanks heating cargo up to 170°C (338°F)

CONVERSION FACTORS

1 m = 3.2808 feet
 1 m³ = 6.28976 US bbls

MACHINERY

1 Hitachi B&W, type SK 42 EF, 5000 BHP
 3 generators of 500 kW each
 2 thermal oil boilers of 1.5 million kcal/h each

SPEED AND CONSUMPTION

Average speed: 12.5 knots
 Consumption at sea: 14.0 mt/day fuel
 1.8 mt/day diesel
 Consumption in port: 3.0 mt/day diesel

TANK CAPACITY

Diesel: 193.6 m³
 Fuel: 668.7 m³
 Ballast: 3,279.2 m³
 Fresh water: 67.1 m³

DISCHARGE CAPACITY

Maximum rate: 930 m³/h 5,850 US bbls/h
 Rate per pump: 310 m³/h 1,950 US bbls/h

