

# M/T Diamond Star



Petro-Nav Inc.  
 204 St. Sacrement Street, Suite 601  
 Montréal (Québec) Canada H2Y 1W8  
 Tel: (514) 843-8800 w Fax: (514) 843-9195  
 E-mail: info@petro.nav.desgagnes.com

Commercial Operator: Petro-Nav Inc., Montréal  
 Tel: (514) 843-8800  
 Fax: (514) 843-9195  
 Built: MTW Shipyard  
 Germany, 1993  
 Official No.: 814363  
 IMO No.: 9040089  
 Call Sign: VCBW  
 Port of Registry: Halifax, NS, Canada  
 Flag: Canadian  
 Type: Oil & Chemical Tanker  
 Class: GL+ 100AS E3 Chemical tanker type II

## MAIN PARTICULARS

GRT: 6,262  
 NRT: 3,154  
 Deadweight: 10,511  
 LOA: 123.71 m 405.87 feet  
 LBP: 118.16 m 387.66 feet  
 Breadth: 17.70 m 58.07 feet  
 Moulded Depth: 10.60 m 34.77 feet  
 Summer Draught SW: 8.36 m 27.43 feet

## COMPLIANCE WITH REGULATIONS

World-wide trading: Solas, Marpol, ISM,  
 USCG for foreign flag, Suez, Panama;  
 St. Lawrence Seaway

TANK CAPACITY	1		2		3		4		5		6		SUB-TOTAL		SLOP TANKS		TOTAL	
	Port	Starboard	Port	Starboard	Port	Starboard	Port	Starboard	Port	Starboard	Port	Starboard	M <sup>3</sup>	US BBLS	Port	Starboard	M <sup>3</sup>	US BBLS
100% (in m <sup>3</sup> )	693	693	914	914	980	980	980	980	980	980	860	860	10,814	68,018	137	185	10,814	68,018
98% (in m <sup>3</sup> )	679	679	896	896	960	960	960	960	960	960	843	843	10,596	66,647	134	181	10,596	66,647

w Double hull, SBT  
 w Seven cargo segregations  
 w Thermal oil heat exchanger for cargo and heating coils for slop tanks

w Tank coating: epoxy  
 w Closed loading system

w Free float Heinrich ullage system for cargo tanks  
 w Loading programme including stability calculation  
 w 95% & 98% level alarms for cargo tanks

## CONVERSION FACTORS

1 m = 3.2808 feet  
 1 m<sup>3</sup> = 6.28976 US bbls

## MACHINERY

1 Man B&W, 6L35MC, 5,032BHP (3,700 kW) & shaft generator  
 3 generators Deutz KHD TBD 604BV8, 595 kW/h each  
 BOW TRUSTER STT 330LK, 410 kW

## SPEED AND CONSUMPTION

Average speed: 12.5 knots  
 Consumption at sea: 14.0 mt/day fuel  
 1.0 mt/day diesel  
 Consumption in port: 3.0 mt/day diesel

## TANK CAPACITY

Diesel: 115 m<sup>3</sup>  
 Fuel: 325 m<sup>3</sup>  
 Ballast: 3,295 m<sup>3</sup>  
 Fresh water: 130 m<sup>3</sup>

## DISCHARGE CAPACITY

Maximum rate: 1,200 m<sup>3</sup>/h 7,548 US bbls/h  
 Rate per pump: 220 m<sup>3</sup>/h 1,384 US bbls/h

